



Our “Oil Pumper” **BLACK** line has the high slip performance and exceptional durability you need for long unattended reliability.

TEFC Cast Iron

3 - 100HP

6 Poles

5% - 8% Slip

Design “D”



Standard Features:

3 Phase

230/460/796V

1045 Steel shafts up to 324T

4140 Steel shafts 324T and up

Roller Bearings on 404T and up

F1, F2 convertible (Shipped F2)

Split conduit box is 90° rotatable

Meeting IP55 protection rating

One-Way Condensate drain plugs

Stainless Steel Nameplates

Oversized Bearings on both ends

Continuous duty (S1)

Vacuum Impregnated

Class F insulation system

Class H impregnation resin

40° C Ambient (3300 Feet)

Designed to Class B temperature rating

Stock Models

HP	Sync. Speed	Model Number	List Price
3	1200	BK3-CI-TF-213T-6-B-G-3	787
5	1200	BK3-CI-TF-215T-6-B-G-5	979
7.5	1200	BK3-CI-TF-254T-6-BR-G-7.5	1289
10	1200	BK3-CI-TF-256T-6-BR-G-10	1539
15	1200	BK3-CI-TF-284T-6-BR-G-15	2058
20	1200	BK3-CI-TF-286T-6-BR-G-20	2272
25	1200	BK3-CI-TF-324T-6-BR-G-25	2808
30	1200	BK3-CI-TF-326T-6-BR-G-30	3314
40	1200	BK3-CI-TF-364T-6-BR-G-40	4177
50	1200	BK3-CI-TF-365T-6-BR-G-50	4650
60	1200	BK3-CI-TF-404T-6-RR-G-60	5876
75	1200	BK3-CI-TF-405T-6-RR-G-75	6661
100	1200	BK3-CI-TF-444T-6-RR-G-100	10158

Call for models not listed

Version 2.0

Techtop Industries Inc.
7000 Peachtree Dunwoody Road
Building 12, Suite 200
Atlanta, GA 30328
866-204-1498 Fax



Need help?

Ready to order?

Call: 678-436-5540 or

Email: Info@techttopind.com